IM C401F

MAIN SPECIFICATIONS

GENERAL	
Warm-up time	24 seconds
First copy speed: B/W	6.2 seconds
First copy speed: full colour	7.4 seconds
Continuous output speed	BW: 43 cpm, full colour: 40 cpm
Memory: standard	6 GB
SSD: standard	256 GB
SSD: optional	1 TB
HDD: optional	320 GB
Weight	50 kg
Dimensions: W x D x H	498 x 561 x 590 mm
Power source	220 - 240 V, 50 - 60 Hz
COPIER	
Multiple copying	Up to 999 copies
Resolution	600 dpi
Zoom	From 25% to 400% in 1% steps
PRINTER	
CPU	ApolloLake E3930 1.3 GHz
Printer language: standard	PCL5c PCL6 PostScript 3 (emulation) PDF direct (emulation)
Printer language: option	Genuine Adobe® PostScript®3™ XPS PDF Direct from Adobe®
Print resolution: maximum	1,200 x 1,200/1 bit
Network interface: standard	Ethernet 10 base-T/100 base-TX/1000 base-T, USB Host I/F Type A, USB Device I/F Type B, Bluetooth, Wireless LAN (IEEE 802.11 a/b/g/n/ac)
Network interface: option	Additional NIC (2nd port)
Mobile printing capability	Apple AirPrint, Mopria®, Ricoh Smart Device Connector
Network protocol	TCP/IP (IP v4, IP v6)
Windows® environments	Windows® 10 Windows® 11 Windows® Server 2016 Windows® Server 2019 Windows® Server 2022 Windows® Server 2025
Mac OS environments	Macintosh OS X v11 or later
UNIX environments	UNIX Sun® Solaris HP-UX SCO OpenServer RedHat® Linux Enterprise IBM® AIX
SCANNER	
Scanning speed: SPDF (A4 LEF, 200dpi, B/W full colour)	40 ipm (simplex) - 80 ipm (duplex)
Resolution: maximum	1,200 dpi
File formats	Single Page TIFF, Single page JPEG, Single page PDF, Single page High compression PDF, Single page PDF/A, Multi page TIFF, Multi page PDF, Multi page High compression PDF, Multi page PDF/A, Single page Encryption PDF, Multi page Encryption PDF, Single/multi OCR (optional)
Scan modes	E-mail, Folder, USB, URL, FTP, E-mail, Folder, USB
FAX	
Circuit	PSTN, PBX
Compatibility	ITU-T (CCITT) G3
seconds Modem speed: maximum	33.6 Kbps
8x7.7 line/mm, 200x200 dpi MH MR MMR JBIG	
Scanning speed	80 spm

IM C401F

MAIN SPECIFICATIONS

PAPER HANDLING

Recommended paper size	Standard paper tray(s) (A4, A5, B5), Bypass tray (A4, A5, A6, B5, B6)
Paper input: standard	550 sheets
Paper input: bypass (standard)	100 sheets
Paper input: maximum	2,300 sheets
Paper output: max.	200 sheets
Paper weight	Trays (60 - 163 g/m²), Bypass (60 - 220 g/m²), Duplex (60 - 163 g/m²)
Paper types	Plain paper, Recycled paper, Special paper, Colour paper, Letterhead, Cardstock, Preprinted paper, Bond paper, Coated paper, Envelope, Label paper

ECOLOGY

Power consumption: max.	< 1,350 W
Power consumption: ready	40.6 W
TEC*	0.47 kWh/week

* It is a reference value based on the ENERGY STAR Ver.3.2 test method.

INPUT/OUTPUT TRAYS AND FINISHER OPTIONS

3x 550-sheet paper tray	Paper size: (A4, A5, B5), Paper weight: (60-163 g/m²)
One-bin tray	Tray capacity: (100 sheets), Paper size: (A4, A5, B5), Paper weight: (60-163 g/m²)

OTHER OPTIONS

Cabinet, High cabinet, Low cabinet, Caster table, PostScript 3, Device server unit, File format converter, OCR unit, Enhanced security HDD, Page keeper, Counter I/F unit, NFC card reader, Paperlock

CONSUMABLES

Toner (black)	17,500 prints
Toner (cyan/magenta/yellow)	8,000 prints

Consumable yield based on 5% coverage/A4

For availability of models, options and software, please consult your local supplier.

Ricoh Deutschland GmbH
Vahrenwalder Str. 315
30179 Hannover
Germany

+49 511 67420

www.ricoh.de

RICOH
imagine. change.

All brand and/or product names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The images in this brochure are not real photographs and slight differences in detail might appear, including in relation to colour. Not all services and solutions are available to all customers. Copyright © 2025 Ricoh Europe PLC. All rights reserved. This brochure, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Europe PLC.